



POLYCAB WIRES PVT. LTD.

Industrial Cables LP No. 05/2018-19 Dtd : 16th November 2018

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF						HR	
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	90 Mtrs.	Coils Per Box
0.75	415	48	835	28			875	28
1	540	36	1080	24	2160	12	1135	24
1.5	805	30	1615	16	3230	10	1695	16
2.5	1300	20	2605	12	5210	6	2735	12
4	1945	16	3895	8	7790	4	4090	8
6	2915	8	5830	6	11660	3	6120	6
10			10300	1				
16			16490	1				

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES - FLAME RETARDANT LEAD FREE (FRLF) / FLAME RETARDANT LOW SMOKE (FRLSH) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES - FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HEAT RESISTANT FLAME RETARDANT LOW SMOKE HALOGEN - LEAD FREE CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLF		FRLS-H		FRZH/LSZH/HFFR		HR	
	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	180 Mtrs. (Pouch Packing)	Coils Per Box
0.75	2785	10	2925	10	2995	10		
1	3600	8	3780	8	3870	8	2270	12
1.5	5385	6	5655	6	5790	6	3390	10
2.5	8685	4	9120	4	9335	4	5470	6
4	8655	4	9090	4	9305	4	8180	4
6	12955	3	13600	3	13925	3	12240	3
10	22890	1	24035	1	24610	1		
16	36645	1	38475	1	39395	1		

Notes

- The above rates are exclusive of GST which shall be charged extra.
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.