

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East, Mumbai - 400 093.

Tel. : 022-2837 5642 / 2823 9673

Fax : 2825 8277

E-mail : nnsuri@kei-ind.com

PRICE LIST : DECEMBER-2017**MRP NO. KEI/W&F/LP/17-18/06 DT. 01.12.2017****INDUSTRIAL MULTI STRAND CABLES****HSN CODE : 85.44.60.20****KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | CURRENT (AMPS) | RATE PER 90M COIL | STANDARD PACKING FOR 90MTR. | RATE PER 180M COIL | STANDARD PACKING FOR 180MTR. | RATE PER MTR |
|------------------------|--------------------------|----------------|-------------------|-----------------------------|--------------------|------------------------------|--------------|
| 0.75 | 24/0.20 | 9 | 800 | 28 | 1600 | 12 | 8.89 |
| 1.00 | 32/0.20 | 14 | 1000 | 24 | 2000 | 12 | 11.11 |
| 1.50 | 30/0.25 | 18 | 1500 | 16 | 3000 | 8 | 16.67 |
| 2.50 | 50/0.25 | 24 | 2430 | 12 | 4860 | 6 | 27.00 |
| 4.00 | 56/0.30 | 32 | 3590 | 8 | 7180 | 4 | 39.89 |
| 6.00 | 84/0.30 | 42 | 5460 | 6 | 10920 | 3 | 60.67 |

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | CURRENT (AMPS) | RATE PER 90M COIL | STANDARD PACKING FOR 90MTR. | RATE PER 180M COIL | STANDARD PACKING FOR 180MTR. | RATE PER MTR |
|------------------------|--------------------------|----------------|-------------------|-----------------------------|--------------------|------------------------------|--------------|
| 0.75 | 24/0.20 | 9 | 830 | 28 | 1660 | 12 | 9.22 |
| 1.00 | 32/0.20 | 14 | 1070 | 24 | 2140 | 12 | 11.89 |
| 1.50 | 30/0.25 | 18 | 1590 | 16 | 3180 | 8 | 17.67 |
| 2.50 | 50/0.25 | 24 | 2560 | 12 | 5120 | 6 | 28.44 |
| 4.00 | 56/0.30 | 32 | 3770 | 8 | 7540 | 4 | 41.89 |
| 6.00 | 84/0.30 | 42 | 5680 | 6 | 11360 | 3 | 63.11 |

KEI BANEFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

| CONDUCTOR (AREA SQ.MM) | NO. & SIZE OF WIRE IN MM | CURRENT (AMPS) | RATE PER 90M COIL | STANDARD PACKING FOR 90MTR. | RATE PER 180M COIL | STANDARD PACKING FOR 180MTR. | RATE PER MTR |
|------------------------|--------------------------|----------------|-------------------|-----------------------------|--------------------|------------------------------|--------------|
| 0.75 | 24/0.20 | 9 | 870 | 28 | 1740 | 12 | 9.67 |
| 1.00 | 32/0.20 | 14 | 1130 | 24 | 2260 | 12 | 12.56 |
| 1.50 | 30/0.25 | 18 | 1660 | 16 | 3320 | 8 | 18.44 |
| 2.50 | 50/0.25 | 24 | 2650 | 12 | 5300 | 6 | 29.44 |
| 4.00 | 56/0.30 | 32 | 3870 | 8 | 7740 | 4 | 43.00 |
| 6.00 | 84/0.30 | 42 | 5850 | 6 | 11700 | 3 | 65.00 |

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7TH Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East, Mumbai - 400 093.

Tel : 022-2837 5642 / 2823 9673

Fax : 2825 8277

E-mail : nnsuri@kei-ind.com



PRICE LIST : DECEMBER-2017

MRP NO. KEI/W&F/LP/17-18/06 DT. 01.12.2017

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES **HSN CODE : 85.44.60.20**

KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

| (Rate in Rs. Per 100 Mtrs) | | | | | | | | | | | | |
|----------------------------|---------------------------|--------|--------------------------|----------------|--------------------------|-------------------|-------|---------------------------|--------|----------------|--------------------------|-------------------|
| SQ.MM | COND. CONST. (NO./DIA.MM) | AMP.s. | STD. PACK OF100 MTR COIL | SINGLE CORE FR | SINGLE CORE HRFR 105 Deg | SINGLE CORE FRLSH | SO.MM | COND. CONST. (NO./DIA.MM) | AMP.s. | SINGLE CORE FR | SINGLE CORE HRFR 105 Deg | SINGLE CORE FRLSH |
| 0.5 | 16/0.20 | 6 | 24 | 670 | 700 | 720 | 35 | 276/0.4 | 125 | 38700 | 40600 | 41600 |
| 0.75 | 24/0.20 | 9 | 24 | 890 | 930 | 960 | 50 | 396/0.4 | 165 | 55500 | 58300 | 59700 |
| 1.0 | 32/0.20 | 14 | 20 | 1110 | 1170 | 1190 | 70 | 354/0.5 | 240 | 77800 | 81700 | 83600 |
| 1.5 | 30/0.25 | 18 | 16 | 1670 | 1750 | 1800 | 95 | 484/0.5 | 300 | 103000 | 108200 | 110700 |
| 2.5 | 50/0.25 | 24 | 12 | 2700 | 2850 | 2900 | 120 | 608/0.5 | 325 | 131700 | 138000 | 142000 |
| 4.0 | 56/0.30 | 32 | 8 | 3990 | 4200 | 4300 | 150 | 750/0.5 | 352 | 165000 | 173000 | 177000 |
| 6 | 84/0.30 | 42 | 4 | 6070 | 6350 | 6550 | 185 | 925/0.5 | 400 | 200000 | 210000 | 215000 |
| 10 | 80/0.40 | 55 | 1 | 11150 | 11700 | 12000 | 240 | 1210/0.5 | 475 | 264000 | 277000 | 284000 |
| 16 | 126/0.40 | 75 | 1 | 17450 | 18300 | 18800 | 300 | 1527/0.5 | 500 | 329000 | 345000 | 354000 |
| 25 | 196/0.40 | 100 | 1 | 27700 | 29100 | 29800 | 400 | 2036/0.5 | | 429000 | 450000 | 461000 |

KEI FLEXIBLE PVC INSULATED MULTICORE PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

| SQ.MM | COND. CONST. (NO./DIA. MM) | AMP.s. | 2 CORE | 3 CORE | 4 CORE | 5 CORE | 6 CORE | 7 CORE | 10 CORE | 12 CORE | 14 CORE | 16 CORE | 19 CORE | 24 CORE |
|-------|----------------------------|--------|--------|--------|--------|--------|--------|--------|---------|---------|---------|---------|---------|---------|
| 0.5 | 16/0.20 | 6 | 2000 | 2650 | 3300 | 4500 | 5200 | 5650 | 8800 | 10150 | 11600 | 13200 | 15250 | 19550 |
| 0.75 | 24/0.20 | 9 | 2700 | 3500 | 4500 | 6200 | 7050 | 7800 | 11850 | 13750 | 15850 | 18100 | 21000 | 26850 |
| 1.0 | 32/0.20 | 14 | 2950 | 4050 | 5300 | 7300 | 8650 | 9700 | 14650 | 16950 | 19650 | 22400 | 25950 | 33100 |
| 1.5 | 30/0.25 | 18 | 4050 | 5650 | 7300 | 10100 | 11900 | 13350 | 19850 | 23350 | 27000 | 30850 | 35850 | 45900 |
| 2.5 | 50/0.25 | 24 | 6550 | 9100 | 11900 | 16100 | 19000 | 21300 | 31400 | 37200 | 43500 | 49400 | 57800 | 73800 |
| 4.0 | 56/0.3 | 32 | 10300 | 14550 | 18600 | 25900 | 29700 | 34400 | 50600 | 60000 | 69600 | 79200 | 93000 | 119500 |
| 6 | 84/0.3 | 42 | 14800 | 21200 | 28000 | 36750 | | | | | | | | |
| 10 | 80/0.4 | 55 | 25100 | 36000 | 47500 | 62550 | | | | | | | | |
| 16 | 126/0.4 | 75 | 39000 | 55900 | 73800 | | | | | | | | | |
| 25 | 196/0.4 | 100 | 89900 | 118000 | | | | | | | | | | |
| 35 | 276/0.4 | 125 | 125000 | 163000 | | | | | | | | | | |
| 50 | 396/0.4 | 165 | 179000 | 234000 | | | | | | | | | | |
| 70 | 354/0.5 | 240 | 247000 | 325000 | | | | | | | | | | |
| 95 | 484/0.5 | 300 | 430000 | | | | | | | | | | | |
| 120 | 608/0.5 | 325 | | | | | | | | | | | | |

KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

| SQ. MM | COND. CONST. (NO./DIA. MM) | RATE |
|--------|----------------------------|-------|
| 1.5 | 30/0.25 | 6050 |
| 2.5 | 50/0.25 | 9400 |
| 4 | 56/0.3 | 14150 |
| 6 | 84/0.3 | 21150 |
| 10 | 80/0.4 | 34800 |
| 16 | 126/0.4 | 55000 |
| 25 | 196/0.4 | 83150 |

Note :

- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Cartoon as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.